



ONE PIECE OVERHEAD
GARAGE DOOR FITTINGS

ADVANCED COLLECTION

Tilt-A-Dor®



The B&D range of Tilt-A-Dor fittings offer the opportunity to create a door that is harmonic with its surroundings, giving the building a truly unique appearance. With durability and safety being primary concerns, Tilt-A-Dor fittings offers the always exceptional B&D quality, providing you with the opportunity to design a door only limited by your imagination.*

STRONG & DURABLE

ANTI SWAY BRACKET

SUITS LOW HEADROOM

TAILOR YOUR DOOR

SUITS LARGE DOORS



Doors & Openers®

THERE'S SO MUCH MORE BEHIND A B&D DOOR

Call **13 62 63** or visit www.bnd.com.au for further information

*For full warranty conditions see back page.

TRACK FITTINGS

Perfectly suited to larger doors where greater stability is provided through the addition of horizontal tracks to hold the door in the open position so as to minimise protrusion outside the opening.


TILT FITTINGS FEATURES

- New spring restraint feature to ensure that spring movement is contained, and eliminates the possibility of spring separation from the fitting.
- Zinc plated fittings offer greater durability, strength and resistance to corrosion.

- Springs designed to provide optimum performance throughout the working life of the fittings.
- Minimal installation clearances required giving the fittings and jamb the ability to fit where some other garage doors will not.
- Supplied with weatherstrip for fitting to the door panel to help restrict entry of water and leaves.
- Strengthened bearing design for greater durability over the life of the fittings.
- Robust anti-sway bracket to limit the degree of lateral movement.
- Available in a number of configurations to suit both single and double width openings.

TRACK FITTINGS					
	50-T	70-T	100-T	120-T	175-T
Maximum Door Weight	50kg	70kg	100kg	120kg	175kg
Minimum Door Height	1800mm	1850mm	1850mm	1900mm	1900mm
Maximum Door Height	2250mm	2250mm	2250mm	2400mm	2700mm
Finish	Zinc plated	Zinc plated	Zinc plated	Zinc plated	Zinc plated
Spring Restraint Feature	Yes	Yes	Yes	Yes	Yes
Number of springs	2	2	2	4	4
Spring life (Cycles)	20,000	20,000	20,000	20,000	20,000
Weathertrip	Yes	Yes	Yes	Yes	Yes
Headroom (Manually operated doors / With automatic opener)	50mm / 100mm	50mm / 100mm	50mm / 100mm	50mm / 100mm	50mm / 100mm
Sideroom	70mm	70mm	70mm	70mm	90mm

Before proceeding please check the opening measurements against the panel and ensure that the correct fitting has been obtained in regards to door weight.



INSTALLATION CLEARANCES	
	TRACK FITTINGS
Door Width	Opening Width – 20mm
Door Height	Opening Height – 27mm
Headroom	50mm for a manually operated door 100mm with an automatic opener
Sideroom	70mm (Model 50-T, 70-T, 100-T, 120-T) 90mm (Model 175-T)
X	15mm

*As with all types of garage doors, for optimal trouble free performance and safety, we recommend you have your door serviced annually.

YOUR **B&D REPRESENTATIVE IS:**

International Customers call **+61 2 9722 5555**
fax **+61 2 9771 6385** or email **bndint@bnd.com.au**



Doors & Openers®

THERE'S SO MUCH MORE BEHIND A B&D DOOR

B&D Doors has offices servicing all states.
For more details on this product or our other ranges,
call **13 62 63** or visit **www.bnd.com.au**

- For areas within one kilometre of a corrosive environment e.g. salt air or industrial fallout, special care and maintenance are generally required for metal products. Consult B&D or your B&D Accredited Dealer for advice.
- The company reserves the right to make changes or improvements to the products or accessories without notice and without incurring any obligation to make similar changes or improvements to goods previously ordered. Specifications subject to change without notice.
- Prefixed Trademarks are trademarks of B&D Australia Pty Ltd.
- B&D products have many patents and registered designs applicable.
- Details correct at date of publication.
- * Please note that B&D provide the tilt door fittings only, not the actual door panel.
- † Tilt-A-Dor® fittings, in normal residential use are covered by a two year warranty for all components and labour conditional on care and servicing as recommended in the door's handbook. Full details of the warranty are available, on request, from your nearest B&D office.
- ‡ Depends on mounting hole used.

RP0910

an **alesco** company

B&D Doors is a division of B&D Australia Pty Ltd, an Alesco company ABN 25 010 473 971 © 2010 B&D Australia